

# Taps and Adapters

## S

Surge Protection Adapters	S-1
Power Strips	S-2
Outlet Taps	S-3, S-4
Grounding Adapters	S-5
Lampholder Adapters	S-6, S-7



Cooper Wiring Devices offers a full line of surge protection devices, grounded and ungrounded outlet taps, and grounding and lampholder adapters.

Available surge protection designs include cord-connected circuit-breaker switched devices, and plug-in adapters, all manufactured from high-impact-resistant thermoplastics for durability and long-term performance. Each complies with the relevant UL 1449 requirements.



## Surge Protection Adapters

2 Pole, 3 Wire Grounding  
15A 125V  
Plug-In

### Six Outlet Surge Adapters – Plug-In

#### FEATURES

- Provides full three mode surge protection for hot to neutral, hot to ground and neutral to ground (except 1156).
- Center mounting screw provided for permanent attachment to receptacle.
- EMI/RFI filtering minimizes line noise.
- Made of high impact-resistant thermoplastic for long-term durability.
- Coaxial protection provided with “F” styled connectors.
- Telephone/fax/modem protection provided with RJ11-styled telephone ports (4 wire protection).
- \$5,000 Connected Equipment Warranty on 1161, 1162 and 1177CG.
- \$2,500 Connected Equipment Warranty on 1156CG.



1177CG



1161CG

### Six Outlet Surge Adapters – Plug-In

Rating W	V	Description	Clamping Voltage	Joules Total	Maximum Surge Current	Color	Catalog No.
15	125	Full Protection	400V	510	30,000 amps (10kA per mode)	Computer Gray	1177CG
15	125	Full Protection w/Coaxial Jacks	400V	510	30,000 amps (10kA per mode)	Computer Gray	1161CG
15	125	Full Protection w/Telephone Jacks	400V	510	30,000 amps (10kA per mode)	Computer Gray	1162CG
15	125	Basic Protection	400V	170	10,000 amps	Computer Gray	1156CG

COMMERCIAL  
RESIDENTIAL

S-1  
TAPS AND  
ADAPTERS

#### TESTING & CODE COMPLIANCE

· Meet UL 1449 & 498 requirements, file E111219

#### MATERIAL CHARACTERISTICS

Flammability  
rating: V0  
Temperature Rating:  
-20°C to 60°C.

# Power Strips

2 Pole, 3 Wire Grounding  
15A 125V  
Cord-Connected



COMMERCIAL  
RESIDENTIAL

**S-2**  
TAPS AND  
ADAPTERS

**TESTING & CODE COMPLIANCE**  
· Meet UL 1449 & 498 requirements, file E111219, UL 498 requirements

**MATERIAL CHARACTERISTICS**  
Flammability rating: VO  
Temperature Rating: -20°C to 60°C

## Surge Protection Power Strip

### FEATURES

- Portable strip provides 7 surge-protected outlets anywhere for stereos, TVs, computers or other electronic-based equipment.
- Full mode surge protection for hot to neutral, hot to ground and neutral to ground.
- Made of high impact-resistant thermoplastic for long-term durability.
- Comes complete with 14/3 SJT 4-ft portable cord.
- Pilot light on/off switch indicates power to unit.
- Resettable 15 amp circuit breaker.

### Surge Protection Power Strips

Rating W	V	Description	Clamping Voltage	Joules Total	Color	Catalog No.
15	125	Full Protection 7 Outlet w/ Circuit Breaker	400V	70	Ivory	1176V



1176

## Circuit Breaker Switch Power Strip

### FEATURES

- Portable strip converts single outlet to multiple outlets (1875W maximum).
- Made of high impact-resistant thermoplastic for long-term durability.
- Circuit breaker with reset feature shuts off power if overloaded.

### Circuit Breaker Switch Power Strip

Rating W	V	Description	Cord Type	Cord Length	Color	Catalog No.
15	125	7 Outlet	14/3 SJT	4' (1.22m)	Ivory	1126V
15	125	6 Outlet	14/3 SJT	3' (0.91m)	Ivory	1136V



1126



1136



# Outlet Taps

2 Pole, 3 Wire Grounding  
15A 125V

## Plug-In Outlet Taps

### FEATURES

- Molded of high impact-resistant plastic for long-term durability
- Six outlet taps provide center mounting screw for permanent attachment to receptacle (1146 only).
- Lighted tap has long-life neon bulb built into body that lights when plugged in.

COMMERCIAL  
RESIDENTIAL

**S-3**  
TAPS AND  
ADAPTERS



1146



1147



4402



1482

### TESTING & CODE COMPLIANCE

- UL Listed, file E15054,
- Meets all UL498 requirements,
- CSA certified, file 2054 (6224-01),
- Meet CSA requirements,
- C22.2 no. 42
- NOM Certified

### MATERIAL CHARACTERISTICS

Flammability rating: VO  
Temperature Rating: -20°C to 60°C

### Six Outlet Taps - Grounding

Rating		NEMA	Description	Color	Catalog No.
W	V				
15	125	5-15R	Duplex Receptacle to 6 Outlets	Brown Ivory White	1146B 1146V 1146W

### Three Outlet Taps - Grounding

Rating		NEMA	Description	Color	Catalog No.
W	V				
15	125	5-15R	Single Receptacle to 3 Outlets	Brown Ivory White	1147B 1147V 1147W

### Lighted Three Outlet Taps - Grounding

Rating		NEMA	Description	Color	Catalog No.
W	V				
15	125	5-15R	Lighted - Single Receptacle to 3 Outlets	Ivory White	1147LTV 1147LTW

### Heavy Duty Three Outlet Taps - Grounding

Rating		NEMA	Description	Color	Catalog No.
W	V				
15	125	5-15R	Heavy Duty Single Receptacle to 3 Outlets	Orange	4402RN

Not for use in wet locations.

### Three Outlet Cube Taps - Grounding

Rating		NEMA	Description	Color	Catalog No.
W	V				
15	125	5-15R	Single Receptacle to 3 Outlets	Brown Ivory White	1482B 1482V 1482W



5-15R

# Outlet Taps

2 Pole, 3 Wire  
15A 125V  
Non-Grounding



COMMERCIAL  
RESIDENTIAL

## S-4 TAPS AND ADAPTERS

### TESTING & CODE COMPLIANCE

- UL Listed, file E15054, Meets all UL498 requirements, CSA certified, file 2054 (6224-01), Meet CSA requirements, C22.2 no. 42
- NOM Certified

### MATERIAL CHARACTERISTICS

Flammability  
rating: VO  
Temperature Rating:  
-20°C to 60°C

## Plug-In Outlet Taps

### FEATURES

- Molded of high impact-resistant plastic for long-term durability
- Swivel adapters hug cords close to wall in tight-fitting places such as behind furniture and office equipment.

#### Six Outlet Taps

Rating		NEMA	Description	Color	Catalog No.
W	V				
15	125	1-15R	Duplex Receptacle to 6 Outlets	Brown Ivory White	1746B 1746V 1746W

#### Three Outlet Taps

Rating		NEMA	Description	Color	Catalog No.
W	V				
15	125	1-15R	Single Receptacle to 3 Outlets	Brown Ivory White	1747B 1747V 1747W

#### Swivel Three Outlet Taps

Rating		NEMA	Description	Color	Catalog No.
W	V				
15	125	1-15R	Swivel - Single Receptacle to 3 Outlets	Ivory White	1792V 1792W
			Swivel - Single Receptacle to 3 Outlets	Ivory	792V*

#### Three Outlet Cube


Rating		NEMA	Description	Color	Catalog No.
W	V				
15	125	1-15R	Polarized - Single Receptacle to 3 Outlets	Brown White	4400B† 4400W†
15	125	1-15R	Single Receptacle to 3 Outlets	Brown Ivory	780B 780V
15	125	1-15R	Single Receptacle to 3 Outlets	Brown White	400B*† 400W*†

## Outlet Flasher

#### Outlet Flasher

Rating		NEMA	Description	Color	Catalog No.
W	V/AC				
100	125	1-15R	Polarized - Single Receptacle to 1 Outlet (14 to 20 flashes per minute)	Brown	471

\*Not UL Listed † Not CSA Listed



1746



1747



1792



4400



1-15R



## Grounding Adapters

**2 Pole, 2 Wire  
with Grounding Lug  
15A 125V**

### Grounding Adapters

#### FEATURES

- Converts 2 pole polarized outlet to 3 wire grounding outlet.
- Grounding lug fastens to wall plate mounting screw for excellent ground connection.
- Safety tab extends face on adapter to assure grounding plugs cannot be plugged in incorrectly.
- Polypropylene body resists dirt and marring.
- Ribbed body for sure insertion and removal.
- Solid brass blades for long life and low heat rise at full load.



**419**

#### Grounding Adapters

Rating		NEMA	Description	Color	Catalog No.
W	V				
15	125	1-15R	2 Pole Polarized to 3 Wire Grounding	Gray White	419GY 419W

### Three Outlet Grounding Adapters

#### FEATURES

- Converts 2 pole polarized outlet to 3 wire grounding outlets.
- Grounding lug fastens to wall plate mounting screw for excellent ground connection.
- Molded of high impact-resistant thermo-plastic for long term durability.
- Solid brass blades for long life and low heat rise at full load.



**1219**


#### Three Outlet Grounding Adapter

Rating		NEMA	Description	Color	Catalog No.
W	V				
15	125	1-15R	Single Receptacle to 3 Outlets with Grounding Lug	Brown Ivory	1219B 1219V

#### Three Outlet Cube Grounding Adapter

Rating		NEMA	Description	Color	Catalog No.
W	V				
15	125	1-15R	Single Receptacle to 3 Outlets with Grounding Lug	Brown White	SA483B* SA483W*

\*Not NOM certified



**SA483**

#### TESTING & CODE COMPLIANCE

- UL Listed, file E15054 except file E15012 for 419, Meet all UL498 requirements
- NOM Certified

#### MATERIAL CHARACTERISTICS

Flammability rating: VO  
Temperature Rating: -20°C to 60°C



**1-15R**



COMMERCIAL  
RESIDENTIAL

**S-6**  
TAPS AND  
ADAPTERS

## TESTING & CODE COMPLIANCE

· UL Listed, file 15055  
Meet all UL 496 & 498 requirements, CSA certified, file 1739 (6231-04), file 2054 (6224-01) for 700, Meet CSA requirements, C22.2 no. 42 & 43  
· NOM Certified

## MATERIAL CHARACTERISTICS

Temperature Rating:  
-40°C to 65°C

## Lampholder Adapters and Accessories

### FEATURES

- 715 and 718 have threaded husk for clamps, shades or guards.
- Pull chains for 718 control lampholder. Side outlets are always on.
- Outlets on adapters are 2-wire polarized.

### Polarized Medium Base Socket Adapters

Rating W	V/AC	Socket to	Switch	Color	Catalog No.
250	125	One Socket & Two Outlets	Pull Chain	Brown Ivory	718B** 718V**
660	125	One Socket & Two Outlets	Keyless	Brown Ivory	715B** 715V**
660	250	Two Sockets	Keyless	Brown Ivory	700B 700V
660	125	Outlet	Keyless	Brown Ivory	758B† 758V†**
660	125	Outlet	Keyless	Brown	808***††

### Polarized Medium Base Outlet Adapters

Rating W	V/AC	Outlet to	Switch	Color	Catalog No.
660	250	Socket	Keyless	Brown Ivory White	738B 738V 738W

### Polarized Medium Base Adapters

Rating W	V/AC	Description	Switch	Color	Catalog No.
660	250	Medium Base to Mogul	Keyless	Brown	362*†

\*Not UL Listed

\*\*UL498 w/outlet

†Not CSA

††Not NOM



718



715



700



758



808



738



362





COMMERCIAL  
RESIDENTIAL

## S-7 TAPS AND ADAPTERS

### TESTING & CODE COMPLIANCE

- UL Listed, file E15055, CSA certified, file 1739 (6231-04), Meet all UL 496 requirements, Meet CSA requirements, C22.2 no. 43
- NOM certified

### MATERIAL CHARACTERISTICS

Temperature Rating:  
-40°C to 65°C



## Lampholder Adapters

Socket Reducers  
Socket Extensions

### Socket Reducers

#### FEATURES

- Mogul reducer has porcelain body, balance of reducer bodies are molded of heat and impact-resistant material.



332



313



341



1054



475

#### Socket Reducers

Rating		Description	Switch	Color	Catalog No.
W	V/AC				
660	250	Mogul to Medium	Keyless	Brown	332
75	125	Medium to Candelabra	Keyless	Brown	313 <sup>†</sup>
75	125	Medium to Intermediate	Keyless	Brown	322* <sup>†</sup>
75	125	Intermediate to Candelabra	Keyless	Brown	341* <sup>†</sup>

### Socket Extensions

#### FEATURES

- One-piece screwshells with porcelain bases.
- 475 winker flashes 14 to 20 times per minute.

#### Socket Extensions

Rating		Description	Base	Extends	Catalog No.
W	V/AC				
660	250	Phenolic	Medium	1.375" (34.9mm)	1054
15-100	125	Phenolic Winker (14 - 20 flashes per minute)	Medium	1.25" (31.8mm)	475

\*Not UL Listed, Not CSA certified

<sup>†</sup>Not NOM Listed